

## 150KVA Step Down Transformer HiPower Skid Type

### CONSTRUCTED FOR RENTAL APPLICATIONS

This transformer is perfect to be used as a temporary power distribution system in industrial plants for shutdowns and maintenance. The isolation power filter allows for use in the entertainment industry including live events, recreational parks & broadcasting. Construction sites, utility plants, refineries, military & shipyards can also all benefit from this transformer. It's temporary power makes it possible to power remote work areas, job trailers and man-camps in the Oilfields.

### PRODUCT FEATURES

- Aluminum coil windings are of high quality magnet wire
- UL Class 220°C insulation system, 150°C temperature rise under full load
- Weather shields (NEMA Type 3R) for outdoor use
- Every coil is impregnated and baked in polyester resin varnish.
- Standard  $\pm 5\%$  or  $\pm 2 \times 2.5\%$  taps
- UL Listed File No. E108255
- CSA Standard C22.2 No. 47 and certified under File No. LR34493.
- Quality assurance and testing are full compliance with CSA Z299.3 & ISO 9001 programs
- Compliant to NEMA TP-1 Standards



### PRODUCT SPECIFICATIONS

High Side Capacity	600V, 3 phase, 175 Amps
Low Side Capacity	480V, 3 phase, 175 Amps
3R Rated	available
Load Side Disconnect	available
Line Side Disconnect	available
Connectors	Camlock
On Wheels	Yes
Dimensions (W×L×H)	62×41.375×52.25 in.
Weight	1,518 lbs.

